


## NO SKIVE

Ghiere a pressione  
Swaged Ferrules  
Preßfassungen

### PF22

Ghiere per tubo SAE 100 R1AT-R2AT EN 853 1SN-2SN EN 857 2SC EN 854 2TE  
Swaged ferrule for SAE 100 R1AT-R2AT EN 853 1SN-2SN EN 857 2SC EN 854 2TE hose  
Preßfassung für SAE 100 R1AT-R2AT EN 853 1SN-2SN EN 857 2SC EN 854 2TE Schlauch




CODICE	DN TUBO	A	B	PESO g
PF2203	3/16" 5	21	23,5	22,00
PF2204	1/4" 6	23	30	38,00
PF2205	5/16" 8	24	30	38,00
PF2206	3/8" 10	26	31	38,00
PF2208	1/2" 13	29	32	42,00
PF2210	5/8" 16	33	36	60,00
PF2212	3/4" 19	37	42,5	84,00
PF2216	1" 25	46	51	125,00
PF2220	1"1/4 32	59	57,5	248,00
PF2224	1"1/2 38	67	60,5	359,00
PF2232	2" 50	80	74	544,00

Ghiere a pressione  
Swaged Ferrules  
Preßfassungen

### PF23

Ghiere per tubo Termoplastico SAE 100 R7 R8 EN 855 R7 R8 1 Troscela acciaio e EN 857 1SC  
Crimp ferrule for Thermoplastic SAE 100 R7 R8 EN 855 R7 R8 1 steel Braid and EN 857 1SC  
Preßfassung für Thermoplastschlauch SAE 100 R7 R8 EN 855 R7 R8 1 Stanhidrahtgeflecht und EN 857 1SC



CODICE	DN TUBO	A	B	PESO g
PF2303	3/16" 5	14	26,5	9,00
PF2304	1/4" 6	18	30,5	19,00
PF2305	5/16" 8	19	32	19,00
PF2306	3/8" 10	22	33	26,00
PF2308	1/2" 13	26	34	38,00