



Flange SAE J 518 3000 PSI ISO 12151-3 (ISO 6162-1) per Tubi: DIN 20023-4SH EN 856-4SH SAE 100R13 EN 856-R13 SAE 100R15
 SAE J 518 Flanges 3000 PSI ISO 12151-3 (ISO 6162-1) for Hoses: DIN 20023-4SH EN 856-4SH SAE 100R13 EN 856-R13 SAE 100R15
 SAE J 518 Flanschschnitte 3000 PSI ISO 12151-3 (ISO 6162-1) für Schläuche: DIN 20023-4SH EN 856-4SH SAE 100R13 EN 856-R13 SAE 100R15



KF3D

DESCRIZIONE	CODICE	DN	TUBO	C	DN FLANGIA	L	M	D
MFL3 3/4" 19	KF3D1212	3/4"	19	14	3/4"	116,5	54,5	38,00
MFL3 1" 19	KF3D1216	3/4"	19	14	1"	119,5	57,5	44,50
MFL3 1" 25	KF3D1616	1"	25	19	1"	135,5	61,5	44,50
MFL3 1"1/4 25	KF3D1620	1"	25	19	1"1/4	138,5	54,5	50,80
MFL3 1"1/4 32	KF3D2020	1"1/4	32	25	1"1/4	148,5	68,5	50,80
MFL3 1"1/2 32	KF3D2024	1"1/4	32	25	1"1/2	151,5	71,5	60,30
MFL3 1"1/2 38	KF3D2424	1"1/2	38	31	1"1/2	166,5	75	60,30
MFL3 2" 38	KF3D2432	1"1/2	38	31	2"	169,5	78	71,40
MFL3 2" 50	KF3D3232	2"	50	42	2"	183,5	79,5	71,40


Flange SAE J 518 3000 PSI ISO 12151-3 (ISO 6162-1) per Tubi: DIN 20023-4SH EN 856-4SH SAE 100R13 EN 856-R13 SAE 100R15
 SAE J 518 Flanges 3000 PSI ISO 12151-3 (ISO 6162-1) for Hoses: DIN 20023-4SH EN 856-4SH SAE 100R13 EN 856-R13 SAE 100R15
 SAE J 518 Flanschschnitte 3000 PSI ISO 12151-3 (ISO 6162-1) für Schläuche: DIN 20023-4SH EN 856-4SH SAE 100R13 EN 856-R13 SAE 100R15



KF39

DESCRIZIONE	CODICE	DN	TUBO	C	DN FLANGIA	L	M	D	H
3 90 3/4" 19	KF391212	3/4"	19	14	3/4"	127,5	65,5	38,00	58,00
3 90 1" 19	KF391216	3/4"	19	14	1"	127,5	65,5	44,50	61,00
3 90 1" 25	KF391616	1"	25	19	1"	158	84	44,50	67,00
3 90 1"1/4 25	KF391620	1"	25	19	1"1/4	158	84	50,80	69,50
3 90 1"1/4 32	KF392020	1"1/4	32	25	1"1/4	180,5	100,5	50,80	79,50
3 90 1"1/2 32	KF392024	1"1/4	32	25	1"1/2	182	102	60,30	87,00
3 90 1"1/2 38	KF392424	1"1/2	38	31	1"1/2	208,5	117	60,30	99,00
3 90 2" 38	KF392432	1"1/2	38	31	2"	218	126,5	71,40	104,00
3 90 2" 50	KF393232	2"	50	41	2"	248,5	144,5	71,40	122,50

Flange SAE J 518 3000 PSI ISO 12151-3 (ISO 6162-1) per Tubi: DIN 20023-4SH EN 856-4SH SAE 100R13 EN 856-R13 SAE 100R15
 SAE J 518 Flanges 3000 PSI ISO 12151-3 (ISO 6162-1) for Hoses: DIN 20023-4SH EN 856-4SH SAE 100R13 EN 856-R13 SAE 100R15
 SAE J 518 Flanschschnitte 3000 PSI ISO 12151-3 (ISO 6162-1) für Schläuche: DIN 20023-4SH EN 856-4SH SAE 100R13 EN 856-R13 SAE 100R15



KF34

DESCRIZIONE	CODICE	DN	TUBO	C	DN FLANGIA	L	M	D	H
3 45 3/4" 19	KF341212	3/4"	19	14	3/4"	132,5	70,5	38,00	27,50
3 45 1" 25	KF341616	3/4"	19	14	1"	134,5	72,5	44,50	29,50
3 45 1" 19	KF341216	1"	25	19	1"	159	85	44,50	28,50
3 45 1"1/4 25	KF341620	1"	25	19	1"1/4	161	87	50,80	30,50
3 45 1"1/4 32	KF342020	1"1/4	32	25	1"1/4	181,5	101,5	50,80	34,50
3 45 1"1/2 32	KF342024	1"1/4	32	25	1"1/2	187	107	60,30	37,50
3 45 1"1/2 38	KF342424	1"1/2	38	31	1"1/2	212,5	121	60,30	41,50
3 45 2" 38	KF342432	1"1/2	38	31	2"	233,4	142	71,40	58,50
3 45 2" 50	KF343232	2"	50	41	2"	261,5	157,5	71,40	58,50