


HYDROWEB


Flange SAE J 518 6000 PSI ISO 12151-3 (ISO 6162-2) per Tubi: DIN 20023-4SH EN 856-4SH SAE 100R13 EN 856-R13 SAE 100R15
 SAE J 518 Flanges 6000 PSI ISO 12151-3 (ISO 6162-2) for Hoses: DIN 20023-4SH EN 856-4SH SAE 100R13 EN 856-R13 SAE 100R15
 SAE J 518 Flanschschnüsse 6000 PSI ISO 12151-3 (ISO 6162-2) für Schläuche: DIN 20023-4SH EN 856-4SH SAE 100R13 EN 856-R13 SAE 100R15



KF6D

DESCRIZIONE	CODICE	DN	TUBO	C	DN FLANGIA	L	M	D
MFL6 3/4" 19	KF6D1212	3/4"	19	14	3/4"	124,5	62,5	41,30
MFL6 1" 19	KF6D1216	3/4"	19	14	1"	129	67	47,60
MFL6 1" 25	KF6D1616	1"	25	19	1"	146,5	72,5	47,60
MFL6 1"1/4 25	KF6D1620	1"	25	19	1"1/4	151	77	54,00
MFL6 1"1/4 32	KF6D2020	1"1/4	32	25	1"1/4	162,5	82,5	54,00
MFL6 1"1/2 32	KF6D2024	1"1/4	32	25	1"1/2	167	87	63,50
MFL6 1"1/2 38	KF6D2424	1"1/2	38	31	1"1/2	183,5	92	63,50
MFL6 2" 38	KF6D2432	1"1/2	38	31	2"	188	96,5	79,40
MFL6 2" 50	KF6D3232	2"	50	41	2"	202	98	79,40


Flange SAE J 518 6000 PSI ISO 12151-3 (ISO 6162-2) per Tubi: DIN 20023-4SH EN 856-4SH SAE 100R13 EN 856-R13 SAE 100R15
 SAE J 518 Flanges 6000 PSI ISO 12151-3 (ISO 6162-2) for Hoses: DIN 20023-4SH EN 856-4SH SAE 100R13 EN 856-R13 SAE 100R15
 SAE J 518 Flanschschnüsse 6000 PSI ISO 12151-3 (ISO 6162-2) für Schläuche: DIN 20023-4SH EN 856-4SH SAE 100R13 EN 856-R13 SAE 100R15



KF69

DESCRIZIONE	CODICE	DN	TUBO	C	DN FLANGIA	L	M	D	H
6 90 3/4" 19	KF691212	3/4"	19	14	3/4"	127,5	65,5	41,30	62,00
6 90 1" 19	KF691216	3/4"	19	14	1"	127,5	65,5	47,60	68,00
6 90 1" 25	KF691616	1"	25	19	1"	158	84	47,60	74,00
6 90 1"1/4 25	KF691620	1"	25	19	1"1/4	156	82	54,00	83,50
6 90 1"1/4 32	KF692020	1"1/4	32	25	1"1/4	182	102	54,00	93,00
6 90 1"1/2 32	KF692024	1"1/4	32	25	1"1/2	182	102	63,50	101,50
6 90 1"1/2 38	KF692424	1"1/2	38	31	1"1/2	213,5	122	63,50	110,00
6 90 2" 38	KF692432	1"1/2	38	31	2"	215,5	124	79,40	126,00
6 90 2" 50	KF693232	2"	50	41	2"	250,5	146,5	79,40	141,00

Flange SAE J 518 6000 PSI ISO 12151-3 (ISO 6162-2) per Tubi: DIN 20023-4SH EN 856-4SH SAE 100R13 EN 856-R13 SAE 100R15
 SAE J 518 Flanges 6000 PSI ISO 12151-3 (ISO 6162-2) for Hoses: DIN 20023-4SH EN 856-4SH SAE 100R13 EN 856-R13 SAE 100R15
 SAE J 518 Flanschschnüsse 6000 PSI ISO 12151-3 (ISO 6162-2) für Schläuche: DIN 20023-4SH EN 856-4SH SAE 100R13 EN 856-R13 SAE 100R15



KF64

DESCRIZIONE	CODICE	DN	TUBO	C	DN FLANGIA	L	M	D	H
6 45 3/4" 19	KF641212	3/4"	19	14	3/4"	135,5	73,5	41,30	30,00
6 45 1" 19	KF641216	3/4"	19	14	1"	139,5	77,5	47,50	34,50
6 45 1" 25	KF641616	1"	25	19	1"	164	90	47,60	33,50
6 45 1"1/4 25	KF641620	1"	25	19	1"1/4	169	95	54,00	38,50
6 45 1"1/4 32	KF642020	1"1/4	32	25	1"1/4	191	111	54,00	41,50
6 45 1"1/2 32	KF642024	1"1/4	32	25	1"1/2	197	117	63,50	47,50
6 45 1"1/2 38	KF642424	1"1/2	38	31	1"1/2	222	130,5	63,50	49,00
6 45 2" 38	KF642432	1"1/2	38	31	2"	236	144,5	79,40	61,00
6 45 2" 50	KF643232	2"	50	41	2"	275	171	79,40	64,50